



# 320W 1950 X 992 X 40mm All Black Pv Panels Mono Solar Panel

### **Basic Information**

Place of Origin: China
Brand Name: Linksun
Certification: CE
Model Number: LS-320M
Minimum Order Quantity: 100PCS
Packaging Details: 1pcs/carton
Delivery Time: 5-8days

• Payment Terms: 30% TT in advance, 70% balance before

delivery.

• Supply Ability: 1000pieces per week



## **Product Specification**

• Color: Black

• Dimension: 1950\*992\*40mm

Efficiency: 16.66%
Power: 320W
Temperature Range: -40 ~+85
Warranty: 25 Years
Weight: 23kg

• Material: Monocrystalline

• Number Of Cells: 72(6x12)

• Highlight: 1950 x 992 x 40mm all black pv panels,

all black pv panels 320 watt, 320w mono solar panel

# Linksun all black 320w monocrystalline solar panels

The 320W All Black PV Panels, measuring 1950 x 992 x 40mm, feature monocrystalline solar cells for high efficiency and sleek aesthetics. These panels are perfect for residential and commercial installations, performing reliably in various light conditions. The all-black design enhances visual appeal, seamlessly blending with modern architecture. Durable and low-maintenance, they ensure long-term energy production. Ideal for eco-conscious users, they help reduce electricity costs and carbon footprint, offering a sustainable and efficient energy solution.

#### **Product Features**

#### 1)Widely Use

Ideal for RVs, small houses, ships, household power supplies, commercial buildings, and more. It helps save electricity consumption and will save you more in the future.

#### 2)Reliable and Durable

Corrosion-resistant aluminum frame provides extended outdoor use that ensures the panel can last for decades.

#### 3)Low production cost

The production cost of monocrystalline silicon solar cells is relatively low, and the technology is already very mature, so it has been widely used.

#### **Product Details:**

Model	LS-320M
Maximum Power(Pmax)	320W
Maximum Power Voltage(Vmp)	36.63V
Maximum Power Current(Imp)	8.74A
Open Circuit Voltage(Voc)	45.82V
Short Circuit Current(Isc)	9.42A
Power Tolerance(Positive)	3%
Cell Type	Mono-crystalline
Contract Dimensions(mm)	1950*992*40mm
Weight(KGS)	23kg
Protection Class	IP65
Maximum System Voltage	1000V
Temperature Range	-40 ~85
Module Efficiency STC	16.66%
Cell number	72(6x12)
Front Glass	3.2mm High Transmission Tempered Glass
Frame Type	Anodized Aluminum Alloy
Connector Type	MC4
Output Cables	4 mm <sup>2</sup> ,Length:900mm



#### FAQ

Q1:What's the solar panels warranty?

A: 5 year's warranty. If you have any questions about our quality during use, you can contact us at any time.

Q2:Do you accept OEM/ODM orders?

A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order?

A:Yes,of course.The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company?

A:We are manufacturer and our factory is based in Yuyao,Ningbo.Welcome your visit if you like.

Q5:Where are your goods exported?

A:We can export to all over the world.



# Ningbo Linksun Energy Science & Technology Co., LTD



+8615888168085



sales02@zjlinksun.com



monosolarpanel.com

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China