

Factory Supply 10W,20W,30W Solar Panel Phone Charger

Our Product Introduction

for more products please visit us on monosolarpanel.com

Basic Information

- Place of Origin: China
- Brand Name: Linksun
- Certification: CE
- Model Number: LS-BSA10
- Minimum Order Quantity: 100PCS
- Packaging Details: 1pcs/carton
- Delivery Time: 5-8days
- Payment Terms: 30% TT in advance, 70% balance before delivery.
- Supply Ability: 1000pieces per week



Product Specification

- Product Name: Folding Solar Blanket
- Solar Cell: Monocrystalline Cell
- Application: Fishing, Camping, Picnics, And Hiking, Including On Yachts And RVs.
- Warranty: 5 Years
- Protection Class: IP65
- Product Dimension(Folded): 155*250*5mm
- Product Dimension(Open): 320*250*2.5mm
- Highlight: **20W Solar Panel Phone Charger ,
10W Solar Panel Phone Charger ,
30W Solar Panel Phone Charger**



More Images



Factory Supply 10W,20W,30W Solar Panel Phone Charger

Lightweight Solar Panels For Mobile homes With USB is a compact, efficient option for charging small devices. With two USB ports offering output in direct sunlight, it's ideal for smartphones, tablets, and other USB-powered devices. The charger uses high-efficiency monocrystalline solar panels for reliable performance, even in low light. Its lightweight, foldable design makes it portable and perfect for outdoor activities like hiking or camping. Water-resistant and durable, it's a great eco-friendly solution for on-the-go charging in various weather conditions. A solid choice for those needing reliable, portable power.

Product Features:

1)High Efficiency:

Utilizes monocrystalline solar cells for maximum power conversion and efficiency.

2)Portable and Lightweight:

Compact design easily folds for transport and storage, making it ideal for outdoor activities.

3)Durable Construction:

Built with robust materials to withstand various weather conditions, ensuring reliability and longevity.

Product Details:

Model	LS-BSA10
Maximum Power(Pmax)	10W
Maximum Power Voltage(Vmp)	5V
Maximum Power Current(Imp)	0.56A
Open Circuit Voltage(Voc)	22.4V
Short Circuit Current(Isc)	0.59A
Power Tolerance(Positive)	± 3%
Cell Type	Monocrystalline cell
Contract Dimensions(mm)	Product Dimension(Folded):155*250*5mm Product Dimension(Open):320*250*2.5mm
Weight(KGS)	0.35kg
Protection Class	IP65
Temperature Range	-20°C - 85°C
Standard Test Conditions	1000W/m2, AM1.5, 25°C





FAQ:

Q1:What's the solar panels warranty?

A: 5 year's warranty.If you have any questions about our quality during use,you can contact us at any time.

Q2:Do you accept OEM/ODM orders?

A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order?

A:Yes,of course.The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company?

A:We are manufacturer and our factory is based in Yuyao,Ningbo.Welcome your visit if you like.

Q5:Where are your goods exported?

A:We can export to all over the world.



Ningbo Linksun Energy Science & Technology Co., LTD

+8615888168085

sales02@zjlinksun.com

monosolarpanel.com

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China